

Power Match®, Micro-lite®, Lubrijet® are registered trademarks of BLOUNT EUROPE SA - Oregon Cutting System Division

Accessories for Chainsaws and Pruners - Description of chains



				Chain type	Pitch	Tooth design	Gauge				Bar length
							.043"	.050"	.058"	.063"	
							1.1 mm	1.3 mm	1.5 mm	1.6 mm	
	Micro Chisel	3/8		N143C-K							12" (30 cm)
	Micro Chisel	1/4		E143MC-K							10" (25 cm)
	Micro Chisel	1/4			E650MC-K						up to 16" (40 cm)
	Semi Chisel	3/8 LOW PRO		N143C-K							from 12" to 16" (from 30 to 40 cm)
	Semi Chisel	3/8 LOW PRO			N150C-N						
	Semi Chisel	3/8 LOW PRO			N150C-K						
	Semi Chisel	.325			K250C-N						from 11" to 20" (from 28 to 50 cm)
	Semi Chisel	.325			K250C-K						
	Semi Chisel	.325				K258C-N					
	Semi Chisel	.325				K258C-K					
	Semi Chisel	.325							K263C-N		from 13" to 18" (from 33 to 45 cm)
	Semi Chisel	.325			K250NK-K						
	Chisel	.325			K250L-N	K258L-N	K263L-N				from 11" to 20" (from 28 to 50 cm)
	Semi Chisel	3/8			A350EP-N						up to 36" (up to 90 cm)
	Semi Chisel	3/8				A358EP-N					
	Semi Chisel	3/8							A363EP-N		
	Pro-Chisel	3/8				A358EP-K					from 13" to 24" (from 33 to 60 cm)
	Pro-Chisel	3/8				A358LM-N					
	Pro-Chisel	3/8							A363LM-N		
	Semi Chisel	404							B463EP-N		

HOW TO IDENTIFY A CHAIN	K		50		C		K		072		EOM	
									# ft.		Loop boxes, reels	
	.325"		.050"		Semi-Chisel		Anti-kickback tooth		N° links reel length			
	Pitch		Gauge		Tooth type		Anti-kickback protection					
	A	3/8"	50	.050" (1.3 mm)	C	Semi-Chisel	K				EOM	
	B	.404	58	.058" (1.5 mm)	EP	Type "E" professional (Semi-Chisel)	N				EEF	
	E	1/4"	63	.063" (1.6 mm)	LM	Magna Chisel (PRO-CHISEL)					REM	
	K	.325"	43	.043" (1.1 mm)	MC	Micro Chisel						
	N	3/8"Lo Pro			NK	Narrow Kerf						

Accessories for Chainsaws and Pruners - Description of chains



										
			Electric chainsaws	Petrol chainsaws						Description
				< 35 cc	35 - 45 cc		45 - 60 cc		> 60 cc	
●	●		●	●	●					Recommended for small and medium displacement chainsaws. Clean cut, high performance. Installed on pruner chainsaws.
●			●	●	●					Compact, lightweight and strong. The bar-chain combination offers a weight reduction of around 15% compared to a traditional chain.
●	●		●	●	●					Maximum performance level. Ideal for intensive pruning work.
●			●	●	●					Developed for DIY applications. Guarantees low vibration and maximum safety thanks to the anti-kickback tooth.
	●	●			●	●	●	●		Lightweight and high performance. This chain was developed for professionals who need an .325" pitch chainsaw.
	●	●			●	●	●			Developed for lightweight chainsaws, guarantees optimal performance and low power absorption.
	●	●			●	●	●			Developed for professional users requiring an .325" pitch chainsaw.
		●				●	●	●	●	Featuring high performance and strength, this chain is specifically designed for demanding professional applications.
		●				●	●	●	●	The 3/8 chisel chain has always been the benchmark for professional users.
		●						●	●	Designed to handle the heaviest duty applications. Unstoppable and super strong.

Pitch	EMAK	OREGON	CARLTON	WINDSOR						
1/4	E650MC-K	25AP	E1MC-BL	50K	90°	30°	.025	85° - 90°	60°	5/32" - 4.0 mm
3/8 LP	N143C-K	90SG	N4C-BL	43RG	90°	35°	.025	85° - 90°	60°	5/32" - 4.0 mm
3/8 LP	N150C-N	91VXL	N1C	50R						
3/8 LP	N150C-K	91VG	N1C-BL	50RG						
.325	K250C-N/K	20BPX	K1C-K1C-BL	50J - 50JG	90°	30°	.025	80° - 90°	60°	3/16" - 4.8 mm
.325	K258C-N/K	21BPX	K2C-K2C-BL	58J - 58JG						
.325	K263C-N	22BPX	K3C	63J - 63JG						
.325	K250NK	95VPX	K1NK-BL	50JSG						
.325	K250L-N	20LPX	K1L	50JL						
.325	K258L-N	21LPX	K2L	58JL	80°	30°	.025	85° - 90°	60°	11/64" - 4.5 mm
.325	K263L-N	22LPX	K3L	63JL						
3/8	A350EP-N	72D - 72DP	A1EP	50A	90°	35°	.025	85° - 90°	60°	7/32" - 5.5 mm
3/8	A358EP-N	73D - 73DP	A2EP	58A						
3/8	A363EP-N	75D - 75DP	A3EP	63A						
3/8	A358EP-K	73V	A2EP-GL							
3/8	A358LM-N	73LGX	A2LM	58APL	80°	30°	.025	80° - 90°	60°	7/32" - 5.5 mm
3/8	A363LM-N	75LGX	A3LM	63APL						

Accessories for Chainsaws and Pruners - Guide-bars and chains



		Guide bars		Chains			Reels Emak 100"		Reels Emak 25"		Oleo-Mac new references		Machines																				
		Length	Part code	Pitch x gauge	N. links Type	Part code	Type	Part code	N. links Type	Part code	Type	Part code	GS 220 Li-Ion	GS 30	GS 250	GS 360	GS 35 C - GS 350 C	937 P.S. - GS 370 P.S.	941 C - GS 410 C - GS 41 - GS 411	941 CX - GS 410 CX - GS 41 - GS 411	GS 44 - GS 440 - GS 45 - GS 451	947 - 952 - GS 520	GS 51 - GS 510 - GS 56 - GS 560	956	962	GS 650 - GS 651	GS 720	GS 200 E	EP 90 - EP 100 - EP 120 - PPX 271				
PS		16" - cm 41	50180029R*	.3/8" x .050" (1.3mm)	56-91 PS	3063006*												●	○	○													
		10" - cm 25	63090030R	.3/8" x .043" (1.1mm)	39-90 SG		N143C-K-100REM	3063037A	N143C-K-025REM	3063023A	N143C-K-039E	30629019A																				●	
		12" - cm 30	54050043	.3/8" x .043" (1.1mm)	45-90 PX		N143C-K-100REM	3063037A	N143C-K-025REM	3063023A	N143C-K-045E	30629041		●																			
		10" - cm 30	3061025R	.1/4" x .043" (1.1mm)	A4SMB	3062055R									●																		
		10" - cm 30	3061026R	.1/4" x .043" (1.1mm)	A4SMB	3062055R										●																	
		12" - cm 30	50030232R	.3/8" x .050" (1.3mm)	45-91 VG						N150C-K-045E	30629013A		●			●																
											N150C-N-045E	30629031A		○			○																
		14" - cm 35	093500313R	.3/8" x .050" (1.3mm)	50-91 VG						N150C-K-050E	30629036A																					
		14" - cm 35	50030190R	.3/8" x .050" (1.3mm)	52-91 VG						N150C-N-050E	30629032A																					
		14" - cm 35	50030190R	.3/8" x .050" (1.3mm)	52-91 VG						N150C-K-052E	30629015A					●	●	○	○												○	
Bar with sprocket nose		14" - cm 35	50030190R	.3/8" x .050" (1.3mm)	53-91 VG					N150C-N-052E	30629033A				○	○	○	○															
										N150C-K-053E	30629016A					●																	
										N150C-N-055E	30629034A																						
										N150C-K-056E	30629017A																						
										N150C-N-056E	30629035A																						
		16" - cm 41	50052012R	.3/8" x .050" (1.3mm)	57-91 VG						N150C-K-057E	30629018A					●	●	○	●												●	
		16" - cm 41	004001108R	.3/8" x .050" (1.3mm)	57-91 VG						N150C-K-057E	30629018A																					
		16" - cm 41	50062006R	.325" x .050" (1.3mm)	66-95 VP						K250C-K-066E	30629004A																					
		16" - cm 41	093800065	.325" x .050" (1.3mm)	66-95 VP		K250C-K-100REM	3063015A	K250C-N-025REM	3063030A	K250C-K-066E	30629004A								●	●												
		18" - cm 46	50230058R	.325" x .050" (1.3mm)	72-95 VP		K250C-N-100REM	3063014A			K250C-K-066E	30629004A												●									
		18" - cm 46	50310206R	.325" x .050" (1.3mm)	72-95 VP						K250C-K-072E	30629027A								○													
		16" - cm 41	094600275R	.325" x .058" (1.5mm)	66-21 BP	001000710R					K250C-K-072E	30629027A								●													
		18" - cm 46	094600285R	.325" x .058" (1.5mm)	72-21 BP						K258C-K-072E	30629007A								●													
		20" - cm 51	50082021R*	.325" x .058" (1.5mm)	78-21 BP						K258C-K-078E	30629008A									○		○	○									
		20" - cm 51	50310207R	.325" x .058" (1.5mm)	78-21 BP		K258C-N-100REM	3063017A	K258C-N-025REM	3063032A	K258C-K-078E	30629008A										●											
		15" - cm 38	50012051*	.325" x .058" (1.5mm)	64-21 LP		K258C-K-100REM	3063018A			K258C-K-064E	30629039A											○		○	○							
		16" - cm 41	50012035R	.325" x .058" (1.5mm)	66-21 BP	001000710R																			●	○							
		18" - cm 46	50012036R	.325" x .058" (1.5mm)	72-21 BP						K258C-K-072E	30629007A													●	○							
		20" - cm 51	50012037R	.325" x .058" (1.5mm)	78-21 BP						K258C-K-078E	30629008A													●	○							
		18" - cm 46	50092020R *	.3/8" x .058" (1.5mm)	68-73 DP						A358EP-K-068E	30629001A														○	○						
		18" - cm 46	50022010R	.3/8" x .058" (1.5mm)	68-73 DP						A358EP-K-068E	30629001A															○	●					
		20" - cm 51	50022011R	.3/8" x .058" (1.5mm)	72-73 DP						A358EP-K-072E	30629002A															○	●					
		22" - cm 56	50022012*	.3/8" x .058" (1.5mm)	77-73 DP	001000754R*					A358LM-N-072E	30629022*															○	○					
		18" - cm 46	50250106R	.3/8" x .058" (1.5mm)	68-73 DP																						○	○					
		20" - cm 51	50250107R	.3/8" x .058" (1.5mm)	72-73 DP		A358EP-K-100REM	3063009*	A358LM-N-025REM	3063025*	A358EP-K-072	30629002																●					
		24" - cm 61	50250108R	.3/8" x .058" (1.5mm)	84-73 DP		A358EP-N-100REM	3063008A			A358LM-N-072E	30629022*																○					
		18" - cm 46	097000244R*	.3/8" x .058" (1.5mm)	68-73 DP		A358LM-N-100REM	3063010A																									
		18" - cm 46	50310221R	.3/8" x .058" (1.5mm)	68-73 DP																												○
		20" - cm 51	50310177R	.3/8" x .058" (1.5mm)	68-73 DP						A358EP-K-068E	30629001A														●							
		20" - cm 51	097000245R	.3/8" x .058" (1.5mm)	72-73 DP						A358LM-N-072E	30629002A															●						
		25" - cm 64	50022041R*	.3/8" x .058" (1.5mm)	88-73 DP						A358EP-K-088E	30629003A																○					

(1) Non-European countries only. • Standard cutting systems. ° Compatible cutting systems. PS Power Sharp * While stocks last

Accessories for Chainsaws and Pruners - Guide-bars and chains



	Guide bars		Chains			Reels Emak 100"		Reels Emak 25"		Oleo-Mac new references		Machines																							
	Length	Part code	Pitch x gauge	N. links Type	Part code	Type	Part code	N. links Type	Part code	Type	Part code	GS 220 Li-Ion	GS 30	GS 250	GS 360	GS 35 C - GS 350 C	937 - GS 370 - GS 37 - GS 371	937 P.S. - GS 370 P.S.	941 CX - GS 410 CX - GS 41 - GS 411	941 C - GS 410 C - GS 41 - GS 411	GS 44 - GS 440 - GS 45 - GS 451	947 - 952 - GS 520	GS 51 - GS 510 - GS 56 - GS 560	956	962	GS 650 - GS 651	GS 720	GS 200 E	EP 90 - EP 100 - EP 120 - PPX 271						
Bar with stellite nose		10" - cm 25	50030352R	.1/4" x .050" (1.3mm)	60-25 AP		E650MC-K-100REM	3063013A	E650MC-K-025REM	3063029A	E650MC-K-060E	30629021A																							
		18" - cm 46	50022014*	.3/8" x .058" (1.5mm)	68-73 DP		A358EP-K-100REM A358EP-N-100REM A358LM-N-100REM	3063009* 3063008A 3063010A	A358LM-N-025REM	3063025*		A358EP-K-072E	30629002A													○ ○									
		20" - cm 51	50022015R*	.3/8" x .058" (1.5mm)	72-73 DP							A358LM-N-072E	30629022*																○ ○						
		24" - cm 61	50090039R*	.3/8" x .058" (1.5mm)	80-73 LP																								○						
		20" - cm 51	50250111R	.3/8" x .058" (1.5mm)	72-73 DP																														
		24" - cm 61	50250112R	.3/8" x .058" (1.5mm)	84-73 DP																									○					
		28" - cm 71	50250113R	.3/8" x .058" (1.5mm)	92-73 DP																										●				
		30" - cm 76	50250110R*	.3/8" x .058" (1.5mm)	102-73 DP																										●				
		18" - cm 46		.3/8" x .058" (1.5mm)	68-73 DP																									○					
		20" - cm 51	097000247R*	.3/8" x .058" (1.5mm)	72-73 DP											A358EP-K-068E	30629001A															○			
		25" - cm 64	097000249R	.3/8" x .058" (1.5mm)	88-73 DP											A358EP-K-072E	30629002A															●			
		30" - cm 76	098000014R*	.3/8" x .058" (1.5mm)	98-73 DP											A358LM-N-072E	30629022*															○			
																A358EP-K-088E	30629003A																●		

(1) Non-European countries only. • Standard cutting systems. ° Compatible cutting systems. * While stocks last

Supplementary chains	.325" x .063" (1.6mm)	67-22PBX		K263C-N-100REM	3063020A	K263C-N-025REM	3063033*	K263C-N-067E	30629029A
		74-22PBX						K263C-N-074E	30629030A
	.325" x .063" (1.6mm)					K263L-N-025REM	3063034*		
	.3/8" x .063" (1.6mm)	66-75LGX		A363LM-N-100REM	3063012	A363LM-N-025REM	3063027*	A363LM-N-066E	30629025*
		72-75LGX						A363LM-N-072E	30629026*
	.3/8" x .063" (1.6mm)	66-75D-DP		A363EP-N-100REM	3063011A	A363EP-N-025REM		A363EP-N-066E	30629023*
		72-75D-DP						A363EP-N-072E	30629024*
	.3/8" x .050" (1.3mm)	72D-DP		A350EP-N-100REM	3063007A				

Number of chain links in chain roll sizes	Pitch	100" roll	25" roll
	3/8"	1640 links	412 links
	.325"	1848 links	464 links
	.404"	1484 links	372 links
	.1/4"	2392 links	600 links